


## Mod. 4209.B

### WATERPROOF CASE

Industrial waterproof case



METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

L LENGTH	420 mm
W WIDTH	300 mm
D DEPTH	95 mm
LID	35 mm
BASE	60 mm


#### EXTERNAL DIMENSIONS

L LENGTH	457 mm
W WIDTH	367 mm
D DEPTH	118 mm

#### OTHER DATA

WEIGHT EMPTY	2 Kg
WEIGHT WITH FOAM	2.4 Kg
WEIGHT WITH CUSTOM FOAM	Kg
VOLUME	12 lt
BUOYANCY	6.8 Kg/max
OPERATING TEMPERATURE	°C min -33 / max 90

IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

L LENGTH	16 9/16 in
W WIDTH	11 13/16 in
D DEPTH	3 3/4 in
LID	1 3/8 in
BASE	2 3/8 in

#### EXTERNAL DIMENSIONS

L LENGTH	18 in
W WIDTH	14 7/16 in
D DEPTH	4 5/8 in

#### OTHER DATA

WEIGHT EMPTY	4.85 lbs
WEIGHT WITH FOAM	5.29 lbs
WEIGHT WITH CUSTOM FOAM	lbs
VOLUME	3.17 gal
BUOYANCY	14.99 lbs/max
OPERATING TEMPERATURE	°F min -27.4 / max 194

## FEATURES



### PULL RELEASE LATCH

New pull release latch grants additional safety and avoids accidental opening



### SOFT GRIP HANDLE

Load tested handle, reinforced with corrosion proof steel pins



### CORROSION PROOF METAL HINGES WITH LID STAY FEATURES



### FIXING POINTS

Additional fixing points on the lid, available on certain models



**SEALING O-RING**  
(Art. NEOSEAL + nr. art.)



**LID CAN BE SET TO SLIDE-OFF**  
By releasing the back screw, lid becomes set to slide-off when opened at 70°



**ABILITY TO STACK**  
The special design of the bottom and the lid feet, grants a perfect stackability.



**METAL CLIPS**  
Clips metálicos reforzados en los principales puntos para candados.



### **WRITABLE NAME TAG**

PVC waterproof ID removable label



### **AUTOMATIC PURGE VALVE**

Automatic pressure release valve.

## ACCESSORIES



### CONVOLUTED FOAM SET FOR CASE 4209 AND 4216

LIDFOAM.42  
(includes 2 pcs.)



### PATENTED HEAVY DUTY BRASS PADLOCK WITH KEYS

EXPL PADLOCK

Designed to fit snug to the Explorer case mould so as not to swing out



### BLIND INSERT

KIT.EXPL.PLUGS

Kit includes 6 pcs.

Whenever the slots are not going to be used for in-built applications, those can be closed by blind inserts that will give the case a better and finished interior look.



### METAL BRACKET

KIT SUPP.EXPL.

Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly



## PLASTIC BRACKET

KIT SUPP.PLAST.

Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly



## HANDY BACKPACK CARRYING SYSTEM FOR CASES

BACKPACK M

Made of robust tear resistant polyester. Designed with adjustable and comfortable padded shoulder straps and belt.

Provided with an external pocket for small accessories, with Velcro strap.

Ideal wherever a free hand movement is required, like in outdoor activities, extreme sports, emergency, rescue, trekking, industrial field, etc.

Suitable for models 3317, 3818 and 5117.

Color: black.

## SPARE PARTS



### Name tag holder for models from 2712 up

KIN.0496

Includes:

1 transparent name tag holder



### Manual pressure release valve for models from 2712 up

KIN.0495

Includes:

1 black purge valve (+ o-ring + pin)

1 threaded bush

1 snap ring (Seeger)