

# WHEELED HARD CASES

**HL**SERIES

**HEAVENLY LIGHT**

- Improved strength
- Over 30% lighter

4825HL		L	W	D								
		LENGTH	WIDTH	DEPTH	LID	BASE						
Internal dim.	mm	480	370	255	50	205						
	in	18 7/8	14 9/16	10 1/16	1 15/16	8 1/16						
External dim.	mm	520	440	276								
	in	20 1/2	17 5/16	10 7/8								
Weight empty		kg 4,5		lbs 9.92								
Weight w/foam		kg 5,3		lbs 11.68								
Volume		lt 39		gal 10.30								
Buoyancy		kg/max 28,2		lbs/max 62.17								
Temp. rating		°C min -33 max +90		°F min -27.4 max +194								
*Certifications	IP67 - STANAG 4280 (ed. 2) - DEF STAN 81-41 (lev. J) MIL-STD 810G											
Version	<b>B</b>	<b>O</b>	<b>G</b>	<b>D</b>	<b>N</b>	<b>Y</b>	<b>BE</b>	<b>OE</b>	<b>GE</b>	<b>DE</b>	<b>NE</b>	<b>YE</b>
Color												

- Soft grip rubber handle
- Stainless steel reinforced padlockable points
- Automatic purge valve
- Can accommodate BAG-F, DIV4820 or BAG-PC48 and PANEXPL48HL



Wheels with bearings



Automatic purge valve



Optional shipping label holder (Art. KIN.1224)

SUGGESTED OPTIONAL ACCESSORIES	
4825HL	BAG-F
<b>PANEXPL48HL</b> 	
<b>BAG-PC48</b> 	<b>DIV4820</b> 

