


## Mod. 5218.B

### COPOLYMER POLYPROPYLENE WATERPROOF CASE

Heavy duty cases with wheels with ball bearings and telescopic handle. Sealing o-ring and removable lid. Available empty or with layers of pre-cubed foam in the bottom and convoluted foam in the lid.



METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

L LENGTH	520 mm
W WIDTH	285 mm
D DEPTH	180 mm
LID	30 mm
BASE	150 mm


#### EXTERNAL DIMENSIONS

L LENGTH	550 mm
W WIDTH	350 mm
D DEPTH	200 mm

#### OTHER DATA

WEIGHT EMPTY	3.75 Kg
WEIGHT WITH FOAM	4.30 Kg
WEIGHT WITH CUSTOM FOAM	Kg
VOLUME	26.6 lt
BUOYANCY	20 Kg/max
OPERATING TEMPERATURE	°C min -33 / max +90

IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

L LENGTH	20 1/2 in
W WIDTH	11 1/4 in
D DEPTH	7 1/16 in
LID	1 3/16 in
BASE	5 7/8 in

#### EXTERNAL DIMENSIONS

L LENGTH	21 5/8 in
W WIDTH	13 3/4 in
D DEPTH	7 7/8 in

#### OTHER DATA

WEIGHT EMPTY	8.26 lbs
WEIGHT WITH FOAM	9.47 lbs
WEIGHT WITH CUSTOM FOAM	lbs
VOLUME	7.02 gal
BUOYANCY	44.09 lbs/max
OPERATING TEMPERATURE	°F min -27.4 / max +194

## FEATURES



### LID CAN BE SET SLIDE-OFF

By releasing the back screw, lid becomes set to slide-off when opened at 70°



### REINFORCED PADLOCKABLE POINTS

Stainless steel clip-covers, to grant a better resistance to abrasion.



### EASY TO OPEN RELEASE TELESCOPIC HANDLE (5218-5221)



### PULL RELEASE LATCH

New pull release latch grants additional safety and avoids accidental opening



### SHIPPING LABEL HOLDER (OPTIONAL)

Polycarbonate removable label



### AUTOMATIC VALVE

Automatic pressure release valve.



### SOFT GRIP HANDLE

Load tested handle, reinforced with corrosion proof steel pins



### SELF OILING FREE RUNNING WHEELS



### INTERNAL SLOTS

Internal slots for optional panel mounting brackets or panel mounting rings



### SEALING O-RING

(Art. NEOSEAL + nr. art.)



### PVC WATERPROOF I. D. REMOVABLE LABEL

(Art. LABELCOVER + nr. art.)



### WRITABLE NAME TAG

PVC waterproof ID removable label

## ACCESSORIES



### PATENTED HEAVY DUTY BRASS PADLOCK WITH KEYS

EXPL PADLOCK

Designed to fit snug to the Explorer case mould so as not to swing out



### PATENTED COMBINATION PADLOCK

EXPL COMBILOCK

Designed to fit snug to the Explorer case mould so as not to swing out



### BLIND INSERT

KIT.EXPL.PLUGS

Kit includes 6 pcs.

Whenever the slots are not going to be used for in-built applications, those can be closed by blind inserts that will give the case a better and finished interior look.



### TSA APPROVED PADLOCK WITH COMBINATION

EXPL TSA.DIGILOCK

The new TSA approved padlocks allow tsa® airport security agents to open the case without destroying the lock. TSA agents are trained to recognize the travel sentry certified logo and should not break the case lock.



### METAL BRACKET

KIT SUPP.EXPL.

Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly



### PLASTIC BRACKET

KIT SUPP.PLAST.

Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly



MADE IN ITALY