


## Mod. RED2712.BCV

### POLYPROPYLENE CASE RED2712

Tactical pistol cases



METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

L LENGTH	276 mm
W WIDTH	200 mm
D DEPTH	120 mm
LID	35 mm
BASE	85 mm


#### EXTERNAL DIMENSIONS

L LENGTH	316 mm
W WIDTH	270 mm
D DEPTH	143 mm

#### OTHER DATA

WEIGHT EMPTY	1.32 Kg
WEIGHT WITH FOAM	1.46 Kg
WEIGHT WITH CUSTOM FOAM	Kg
VOLUME	6.6 lt
BUOYANCY	4.2 Kg/max
OPERATING TEMPERATURE	°C min -33 / max 90

IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

L LENGTH	10 7/8 in
W WIDTH	7 7/8 in
D DEPTH	4 3/4 in
LID	1 3/8 in
BASE	3 3/8 in

#### EXTERNAL DIMENSIONS

L LENGTH	12 7/16 in
W WIDTH	10 5/8 in
D DEPTH	5 5/8 in

#### OTHER DATA

WEIGHT EMPTY	2.91 lbs
WEIGHT WITH FOAM	3.21 lbs
WEIGHT WITH CUSTOM FOAM	lbs
VOLUME	1.74 gal
BUOYANCY	9.25 lbs/max
OPERATING TEMPERATURE	°F min -27.4 / max 194

## FEATURES



### CORROSION PROOF METAL HINGES WITH LID STAY FEATURES



### INTERNAL SLOTS

Internal slots for optional panel mounting brackets or panel mounting rings



### SEALING O-RING

(Art. NEOSEAL + nr. art.)



### MANUAL PRESSURE RELEASE VALVE

The internal stop ring prevents valve from being completely extracted (Art. PURGEVALVE.B)



### **PVC WATERPROOF I. D. REMOVABLE LABEL**

(Art. LABELCOVER + nr. art.)



### **COUNTERBALANCE SUPPORTS**

(in certain models)