


## Mod. RED3005.BCV

### POLYPROPYLENE CASE RED3005

Tactical pistol cases



METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

L LENGTH	300 mm
W WIDTH	210 mm
D DEPTH	58 mm
LID	20 mm
BASE	38 mm


#### EXTERNAL DIMENSIONS

L LENGTH	326 mm
W WIDTH	269 mm
D DEPTH	75 mm

#### OTHER DATA

WEIGHT EMPTY	1.10 Kg
WEIGHT WITH FOAM	1.20 Kg
WEIGHT WITH CUSTOM FOAM	Kg
VOLUME	4 lt
BUOYANCY	2.10 Kg/max
OPERATING TEMPERATURE	°C min -33 / max 90

IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

L LENGTH	11 13/16 in
W WIDTH	8 1/4 in
D DEPTH	2 5/16 in
LID	13/16 in
BASE	1 1/2 in

#### EXTERNAL DIMENSIONS

L LENGTH	12 13/16 in
W WIDTH	10 9/16 in
D DEPTH	2 15/16 in

#### OTHER DATA

WEIGHT EMPTY	2.42 lbs
WEIGHT WITH FOAM	2.64 lbs
WEIGHT WITH CUSTOM FOAM	lbs
VOLUME	1.05 gal
BUOYANCY	4.62 lbs/max
OPERATING TEMPERATURE	°F min -27.4 / max 194

## FEATURES



### CORROSION PROOF METAL HINGES WITH LID STAY FEATURES



### INTERNAL SLOTS

Internal slots for optional panel mounting brackets or panel mounting rings



### SEALING O-RING

(Art. NEOSEAL + nr. art.)



### MANUAL PRESSURE RELEASE VALVE

The internal stop ring prevents valve from being completely extracted (Art. PURGEVALVE.B)



### **PVC WATERPROOF I. D. REMOVABLE LABEL**

(Art. LABELCOVER + nr. art.)



### **COUNTERBALANCE SUPPORTS**

(in certain models)